



S LUB 20

TECHNICAL INFORMATION – rev 7.4

S LUB is a special lubricant for fiber optical installation for min and micro cable with blowing machine. It's a water emulsion of different kind of polymers.

S LUB is a water base product with high efficiency of lubricant. It's reduce dramatically the friction. S LUB is white liquid little bit viscosity.

S LUB adhere perfectly at the cable surface or at the internal surface of the pipe. It's leave a very tiny film of lubricant and does not make the glue effect. Product Use: Cable and Duct Prelubrication

Suggest Uses quantities for 1.000 mt

diam Ø mm internal pipe	Quantities of product
20 – 30 mm	60 ml
30 - 40 mm	70 ml
40 - 50 mm	100 ml

The real quantities can be change due to a condition of the pipe or how is difficult the pipe long.

Use:

Shake the bottle before use, then put the product inside in the pipe. Then pre-lubricant the pipe with a little piece of sponge.

The product is also suitable for blowing machine with oil dispenser to lubricating the fiber during the pushing.

The S LUB 20, also can be useful to lubricate the fiber optic before or after blowing machine. It's depend on the appliance with iron wheel or with rubber wheel.



CARIMA S.r.l. – C.F. e P. IVA 06727370154
Via dei Brughi, 30/31 – 20060 Gessate (MI) - Italy
Tel. e fax +39 02 9538.4225 - fax +39 02 7005.8164 - cell uff +39 348 6003.588
www.carima.biz info@carima.biz

Technical Specification:

Aspect	White liquid tiny viscosity
Odour	none
Viscosity	120 sec. Ford cup diam. mm 4 at 20C°
Spefigic gravity	1,030 +- 0,03 gr/cm ³
pH	7,5 +- 0,5
Inflammability	non infiammabile
Temperature	-5° + 70° C.
Biodegradability	il prodotto è biodegradabile
Toxic	The product is not toxic.

CONFEZIONI

Cod. VSLUB20025	in scatole da 24 pz da Kg 0,25
Cod. VSLUB2005	in scatole da 12 pz da Kg 0,5
Cod. VSLUB201	in scatole da 15 pz da Kg 1
Cod. VSLUB205,10,20, 25	in tuniche da Kg 5, 10,20 e 25